



# CMCP-OS2400-485 Industrial RS-485 Radio

### Features

- Low Cost
- Class I, Div II
- Secure Communication
- Worldwide Unlicensed 2.4 GHz
- High Power
- Long Range with Extensive Antenna Selection
- 250 Kbps RF Data Rate
- Accommodates ASCII, DF1, Modbus RTU, Modbus ASCII and DNP protocols
- Configurable to Master/Repeater/Remote
- Secure 128-bit proprietary encryption and frequency hopping spread spectrum (FHSS) physical layer



### Overview

The CMCP-OS2400-485 Industrial Radio uses advanced digital signal processing (DSP) to provide the ultimate in performance and reliability. The versatility of the DSP core and small, DIN rail-mountable form factor make the CMCP-OS2400-485 ideally suited for your industrial and utility wireless applications. The radio operates in the license-free 2.4 GHz ISM band and can be used throughout the world with no site licenses or monthly leased line/wireless service fees.

Designed to operate in high-interference environments, the radio combines advanced frequency hopping and digital signal processing technology with outstanding receiver sensitivity and antenna diversity resulting in exceptional noise and interference rejection.

Peer-to-peer addressing and store-and-forward repeaters allow point-to-point, broadcast, and point-multipoint nodes. The RF output levels are user-configurable and 32 data channels allow multiple networks to operate in the same area.

With integrated support for ASCII, DF1, Modbus RTU, Modbus ASCII and DNP, the CMCP-OS2400-485 directly supports your industrial application's RS-232, RS-422 or RS-485 data interfaces. A transparent communications mode is also available as is custom protocol support.

Free Windows®-based software for setup and remote diagnostics is included. The graphical user interface helps make the radio easy to install and operate. The radio allows network-wide radio configuration at one time, saving significant set-up time. Troubleshooting is simplified with remote diagnostics and an extensive context-sensitive online help.

### Ordering Information:

Part No.	-XXX	Description
CMCP-	-ETHERNET	802.3 Ethernet Industrial Radio
	-485	RS-232/422/485 MODBUS RTU and ASCII Industrial Radio

Although care has been taken to assure the accuracy of the data compiled in this publication, SKF CMCP does not assume any liability for errors or omissions. SKF CMCP reserves the right to alter any part of this publication without prior notice.

(5/3/01) Copyright © 1999-2001 by SKF CMCP

ALL RIGHTS RESERVED



# CMCP-OS2400-ETHERNET

## Industrial Ethernet Radio

### Specifications

<b>General</b>	
Size	4.50" W x 4.12" H x 2.32" D
Weight	8 ounces
Operating Temperature	-40°C to +75°C; -40°F to +167°F
Humidity	To 90% RH, non-condensing
Antenna	Two SMA connectors, automatic antenna diversity
Range	Up to 16 miles with high-gain antennas (can be extended with repeaters)
Software	Windows®-based user setup, diagnostic software
<b>Data Interface</b>	
Serial Data Interface	RS-485, RS-422 and RS-232
Communication	Asynchronous half-duplex/full-duplex
I/O Data Rate	1200 bps to 115.2 Kbps full-duplex
Network Topology	Point-to-point, broadcast, point-to-multipoint, store and forward repeater, peer-to-peer
Channels	32 user-selectable
Error Detection/Correction	32 bit CRC with automatic re-send query (ARQ)
Latency	<20 ms
Encryption	128 bit proprietary encryption
<b>Radio Characteristics</b>	
Frequency	2.4-2.4835 GHz for USA; varies for other countries. Frequency hopping spread spectrum (FHSS)
Output Power	1 mW-250 mW, programmable; Max EIRP up to 64 W effective radiated power
Channel Data Rate	250 Kbps
Receiver Sensitivity	-100 dBm @ 5x10 <sup>-4</sup> BER typical
<b>Power</b>	
Supply Voltage	6-24 VDC
Average Power	2.5 W master, 1.25 W remote
<b>Certification</b>	
FCC	FCC Part 15.247
Industry Canada	RSS 210
Europe	ETSI 300.328, ETSI 300.826, EN60950
UL	UL 1604 Class I Division 2, Groups A, B, C and D
CSA	C22.2 No. 213-M1987 , 213-1987