

Condition Monitoring Custom Products

"Vibration Monitoring and Machine Protection Systems"

2911 S. Shore Blvd., Ste. 170, League City, TX 77573 Phone: 281.334.0766 Fax: 281.334.4255

CMCP205 Motor Fin Mounts

Features:

- Available in Four Sizes
- 416 SS (Magnetic)
- Kits Supplied with Adhesive, Dispenser, Mixing Nozzles
- Obtain Meaningful Vibration Data

Description:

The CMCP205 Motor Fin Mounts provide a mounting location for either magnetically mounted or permanently mounted accelerometers on motors where the bearing housing is not accessible. The Fin Mounts are machined from 416 SS and are adhesive mounted between the cooling fins of the motor. The CMCP205 Fin Mounts are provided in four sizes to accommodate a variety of motors and to keep the amount of required adhesive to a minimum. The CMCP205 can be purchased individually, and are available in kits in quantities of 50 or 100. Kits are supplied with adhesive and mixing nozzles.

Ordering Information:

CMCP205	-XX	-XX	Description
<u> </u>	01		1.25" x 0.50"
	02		2.00" x 0.50"
	03		1.75" x 0.25"
	04		1.00" x 0.25"
		50	Kit, Quantity of 50
		100	Kit, Quantity of 100

Optional:

CMCP206		Adhesive Filler	
	CMCP207	Dispenser	
	CMCP208	Mixing Nozzle	





Specifications:

Material: 416 SS (Magnetic)

Pad Thickness: 3/8"

Pad Surface Finish: 32 μ in. RMS

Pad Tap: 1/4-28

Although care has been taken to assure the accuracy of the data compiled in this publication, SKF CMCP does not assume any liability for errors or omissions. SKF CMCP reserves the right to alter any part of this publication without prior notice.

(5/3/01) Copyright © 1999-2001 by SKF CMCP

ALL RIGHTS RESERVED