

Vibration Monitoring and Machine Protection Systems

1010 East Main Street, League City, TX 77573 Phone: 281.334.0766 Fax: 281.334.4255 www.stiweb.com / www.stiwebstore.com

CMCP205 Motor Fin Mounts

Features:

- Available in Four Sizes
- 416 SS (Magnetic)
- Obtain Meaningful Vibration Data



Description:

The CMCP205 Motor Fin Mounts provide a mounting location for either magnetically mounted or permanently mounted accelerometers on motors where the bearing housing is not accessible. The Fin Mounts are machined from 416 SS and are adhesive mounted between the cooling fins of the motor. The CMCP205 Fin Mounts are provided in four sizes to accommodate a variety of motors and to keep the amount of required adhesive to a minimum.

Specifications:

Material: 416 SS (Magnetic)

Pad Thickness: 3/8"

Pad Surface Finish: 32 μ in. RMS

Pad Tap: 1/4-28

Ordering Information:

CMCP205	-XX	-XX	Description
	01		1.25" x 0.50"
	02		2.00" x 0.50"
•	03		1.75" x 0.25"
	04		1.00" x 0.25"

Optional:

CMCP206	Adhesive Filler
CMCP207	Dispenser
CMCP208	Mixing Nozzle